

Hot Air Lance

For Distressed Pavement Repair Preparation



Warms and Dries Pavement

*High temperature, high velocity,
flameless heat lance*

FEATURES AND BENEFITS

- Remove vegetation and flammable debris
- Warm pavement in cool weather
- Dry moist pavement prior to sealing
- Velocity of up to 3000 ft per second
- Smooth and blend the edges of pavement repairs

CRAFCO[®] **INC**
PRESERVATION PRODUCTS PAVEMENT

Delivering Confidence Through Innovation, Quality and Value Since 1976

Hot Air Lance



The Hot Air Lance is used to dry and prepare pavement cracks, potholes and distressed pavement surface for repair. Featuring separate valves which control the mixture of fuel and compressed air at the point of combustion.

The Hot Air Lance is capable of producing heat up to 2,600 degrees with a velocity of 3,000 feet per second. The combustion chamber is constructed from Stainless Steel for lasting durability. All fuel is ignited before exiting the burner tube providing flameless hot air at the point of pavement contact.

The Hot Air Lance comes standard with a wheel kit, a 40ft hose, LP gas regulator, air regulator gauge, water separator, standard Chicago tank fittings, and abrasion wrap with quick connect fittings. Lance weight is approximately 9.2 pounds with a one year warranty against material defects and workmanship.

