



DISSCO® MC-30 TACK COAT

ASPHALT CUTBACK

DISCRIPTION

DISSCO MC-30 is a thin, Medium Cure (MC) asphalt cutback. DISSCO MC-30 is designed to provide superior adhesion for asphalt patches to existing asphalt pavement, brick or concrete. DISSCO MC-30 waterproofs the edges of the patch to prevent water intrusion through the joint and helps prevent pushing and shoving of the patching material by rolling. No heating required.

SURFACE PREPARATION

Surface to be tacked must be clean and dry. Remove dirt and debris by hand or mechanical sweeping or with a high-volume blower to remove dirt, loose rock and vegetation.

APPLICATION

DISSCO MC-30 is supplied ready to use and may be used directly from the container. Apply with a brush, broom, roller or spray equipment. Thin overlays should have a 8" wide band around the perimeter of the patch and apply at a rate of .10 gal/sq. yd. in the center areas. On excavated or utility patch repairs all vertical surfaces of existing pavement should be coated. *Do not apply to wet surfaces and or when rain is imminent.*

CURE TIME

Cure time will vary depending on weather conditions.

STORAGE

DISSCO MC-30 will not freeze and may be stored outdoors. DISSCO Clean tools with petroleum solvent or a good citrus base cleaner immediately after use.

AVAILABILITY

DISSCO CSS1h is available in a concentrate form and is available in bulk and in packaged sizes of 5-gallon pails and 55-gallon drums.

SPECIFICATION

Denver Industrial Sales & Service Co. (DISSCO) Manufactures MC-30 as per the requirements as set forth in ASTM D-2027 for viscosity, flash point and residue properties of the pre blended asphalt base ONLY.

Properties of MC-30 as per ASTM D 2027

Designation	Range	Average Results
Kinematic Viscosity @ 140°F	30 -60	48
Flash Point	100°F min	105°F
Distillate Test	See note below**	N/A
Percent residue by wt (calculated method)	45% min	51%
Base Asphalt Viscosity	800 – 1200	1035
Weight per gallon at 60°F		7.8 lbs

Denver Industrial Sales & Service Company

850 South Lipan Street, Denver, CO 80223

Ph 303-935-2485 Fax 303-935-6787

www.dissco.net

****Note** DISSCO shall not certify the requirements set for distillation range percentages. This exception is due to the non-availability of proper refinery base cutter stocks and due to the hazardous nature of distilling flammable liquids using the distillation procedure set forth in ASTM D-402. Due to these hazards, DISSCO does not perform the procedure set forth in ASTM D-402 and therefore DISSCO will not certify to meet the requirement set for the distillation percentages.

CAUTION

Contains petroleum distillates. Do not use near fire or flame. Use with adequate ventilation. Vapor harmful. Avoid prolonged or repeated contact with skin or breathing of vapor. Close container tightly after each use. Harmful or fatal if swallowed. If swallowed, DO NOT INDUCE VOMITING. Call physician immediately. KEEP OUT OF REACH OF CHILDREN

WARRANTY

DISSCO warrants its products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, DISSCO makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to DISSCO coatings. DISSCO's sole obligation shall be, at its option, to replace, or to refund the purchase price of, the quality of DISSCO coating proved to be defective and DISSCO shall not be liable for any loss or damage, including incidental or consequential damages arising from the use of DISSCO coatings.

For Professional use ONLY.

For further information, please call (303) 935-2485.

**In case of an EMERGENCY involving any DISSCO product please call:
Info-Trac @ 1-800-535-5053**

DANGER



GHS Precautionary Information

Hazard statement: Flammable Liquid and Vapor. May be fatal if swallowed and enters airways.

PPE/Prevention, Obtain special instructions before use. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood.

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention.

Storage Store in accordance with international regulations. Store locked up. CSS1h will freeze, store indoors when freezing temperature are expected.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Warranty, DISSCO warrants its products to be free of defects in materials but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, DISSCO makes no other warranty, express or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to DISSCO coatings. DISSCO's sole obligation shall be, at its option, to replace, or to refund the purchase price of, the quality of DISSCO coating proved to be defective and DISSCO shall not be liable for any loss or damage, including incidental or consequential damages arising from the use of DISSCO coatings.

For further information, please call (303) 935-2485.

**In case of an EMERGENCY involving any DISSCO product please call:
Info-Trac at 1-800-535-5053**

Denver Industrial Sales & Service Company

850 South Lipan Street, Denver, CO 80223

Ph 303-935-2485 Fax 303-935-6787

www.dissco.net