

Performance and Longevity to improve Hot Mix



Increase the Lifespan of your Hot Mix Asphalt

PAVEGRIP®, Hot Mix Adhesion Promoter, is a high-performance anti-stripping additive that dramatically improves adhesion and increases tensile strength.

Our customers see it as a cost-effective additive that is less than half the cost of hydrated lime, adding value to their mixes by improving hot mix performance.

High Performance

Equals Cost-Effectiveness

PAVEGRIP is specially formulated to increase the lifespan of asphalt pavements. Industry studies have shown adhesion promoters can increase a pavement's quality lifespan by over 30%.

These results can be achieved by using as little as one half pound of PAVEGRIP per ton of asphalt mix. Its active formulation can be adapted to even difficult mix designs.

Increases Tensile Strength Ratio

The photos of the core samples, to the right, show an actual mix design with and without PAVEGRIP. It is apparent that the sample without PAVEGRIP exhibits stripping of the asphalt cement from the aggregate. Stripping or loss of adhesion leads to premature pavement failures. PAVEGRIP dramatically improves adhesion and increases the tensile strength ratio of the mix.





Call us today!

PAVEGRIP® is a product of **unique**



Increase Performance and Reduce your Costs



Easy to Add Safe to Use

PAVEGRIP® is a high-performance, low-odor liquid with excellent heat stability, that is added directly into the asphalt.

This can be accomplished at the asphalt terminal or hot mix plant.

Technical Support for your Applications

Authorized UNIQUE representatives will help you determine the proper formulation for PAVEGRIP.

Our goal is to help you design a longer lasting road.

Stringent Quality Control

Our quality control process is designed to ensure you get a consistently superior product.

Product Details

Recommended Dosage: 0.25% to 0.75% based upon the weight of the liquid asphalt cement.

Properties: Viscosity @ 77F cSt 450 - 750°

Specific Gravity @ $77^{\circ}F$ 1.02 ± 0.04 Weight, lbs/gal @ $77^{\circ}F$ 8.50 ± 0.33 Flash Point (ASTM D92) 359°F Pour Point (ASTM D97) $10^{\circ}C/50^{\circ}F$ **PAVEGRIP** is available in:

55 gallon drums 275 gallon totes

In various bulk quantities as required



