SAFETY DATA SHEET

1. Identification	
Product identifier	DISSCO _® 501 Primer
Other means of identification	Asphalt Cutback
Recommended use	Asphalt primer for use with hot applied waterproofing
Recommended restrictions	Not known

Manufacturer/Importer/Supplier/Distributor information

Manufacturer	
Manufacturer:	DISSCO - Denver Industrial Sales and Service Co.
Address:	850 South Lipan Street
	Denver, CO 80223
Contact Name:	Todd Mellema
Telephone:	303-935-2485
E-mail:	todd@dissco.net
INFOTRAC:	1-800-535-5053

2. Hazard(s) identification		
Physical hazards	Flammable liquids	Category 3
Health hazards	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified	
OSHA defined hazards	Not classified	

Lable elements



Signal word	Warning
Hazard statement	Flammable liquid and vapor. May cause drowsiness or dizziness
Prevention	Keep away from heat/spars/open flames/hot surfaces. – No smoking. Use only outdoors or in a well-ventilated area. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors/spray. Wash thoroughly after handling.
Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: use appropriate media for extinction.
Storage	Store in a well-ventilated place. Keep Cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations. See section 13 of this SDS for disposal instructions.
Hazard(s) not otherwise Classified (HNOC)	None known
Supplemental information	None

DISSCO®

3. Composition/information on ingredients

Mixtures

Chemical name	Common Name and synonyms	CAS number	%
ASPHALT		8052-42-4	40 - 60
PETROLEUM NAPHTHA		8008-20-6	40 - 60

Composition comments	Components not listed are either non-hazardous or below the required disclosure threshold.
4. First-aid Measures Inhalation Skin contact	Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing difficulties, oxygen may be necessary. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention, if needed. For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. For minor skin contact, avoid spreading material on unaffected
Eye contact	 skin. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention. Immediately flush eyes with plenty of water for at least 15 minutes. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth thoroughly. Call a POISON CENTER or doctor/physician. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into lungs
Most important Symptoms/effects, acute and Delayed	Not available
Indication of immediate Medical attention and special Treatment needed	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed
General information	IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Get medical attention if symptoms occur. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.
5. Fire-fighting measures Suitable extinguishing media	Foam. Carbon dioxide (CO2). Water fog. Dry chemical powder.
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases
Special protective equipment and precautions for firefighters Fire-fighting Equipment/instructions	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection. In case of fire and/or explosion do not breathe fumes. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Do not get water inside container. Some of these materials, if spilled, may evaporate leaving a flammable residue.
Specific methods	In the event of fire and/or explosion do not breathe fumes

DISSCO®

6. Accidental release measure Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleaning up Environmental precautions	s Keep unnecessary personnel away. Keep upwind. Keep out of low areas. Ventilate closed spaces before entering them. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material Stop the flow of material, if this is without risk. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Never return spills in original containers for re-use. Prevent further leakage or spillage if safe to do so. Do not contaminate water. If this material is spilled into navigable waters and creates a visible sheen, it is reportable to the National Response Center
7. Handling and storage Precautions for safe handling Conditions for safe storage, Including any Incompatibilities	Avoid heat, sparks, open flames and other ignition sources. Avoid breathing dust/fume/gas/mist/vapors/spray. Wear personal protective equipment. Do not use in areas without adequate ventilation. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Do not empty into drains. Hydrogen sulfide, a very highly toxic gas, may be present with this material. Keep face clear of tank and/or tank car openings. Store in a well-ventilated place. Keep container closed. Keep container dry. Keep away from food, drink and animal feeding stuff. Keep out of reach of children. Use care in handling/storage.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit	Values		
<u>Components</u>	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction
PETROLEUM NAPHTHA	TWA	200 mg/m3	Non-aerosol
(CAS 8008-20-6)			
Us. NIOSH: Pocket Guide to	• Chemical Hazards		
Components	Туре	Value	Form
ASPHALT (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume
PETROLEUM NAPHTHA	TWA	100 mg/m3	(CAS 8008-20-6)
(CAS 8008-20-6)			
Biological limit values	No biological exposure limit	ts noted for the ingredient(s)	
Exposure guidelines			
US ACGIH Threshold limit v	alues: Skin designation		
PETROLEUM NAPHTHA (CAS 8008-20-6)	Can be absorbed	through the skin
Appropriate engineering	Provide adequate ventilation, including appropriate local extraction, to ensure that the		
controls	defined occupational exposure limit is not exceeded		
Individual protection measur	es, such as personal protectiv	ve equipment	
Eye/face protection	Wear safety glasses; chemic	cal goggles (if splashing is possi	ble)
Hand protection	Chemical resistant gloves a	re recommended. If contact w	ith forearms is likely wear gaunt
	style gloves.		

OtherIt is a good industrial hygiene practice to minimize shin contact. Wear appropriate clothing
to prevent any possibility of liquid contact and repeated or prolonged vapor contactRespiratory protectionWhen workers are facing concentrations above the exposure limit they must use appropriate
certified respirators

DISSCO®

Thermal hazard	Not Available
General hygiene	When using, do not eat, drink or smoke. Avoid contact with eyes. Avoid contact with skin.
considerations	Wash hands before breaks and immediately after handling the product. Handle in
	accordance with good industrial hygiene and safety practice.
9. Physical and chemical prope	
Appearance	Viscous liquid
Physical state	Liquid
Form	Liquid
Color	Brown – black
Odor	Mild Petroleum Odor
Odor threshold	Not available
рН	Not available
Melting point/freezing point	Not available
Initial boiling point and	≥305° F (151° C), range not available
boiling range	
Flash point	≥ 105° F (≥40.5° C) Closed cup
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper/lower flammability or e	explosive limits
Flammability limit – lower	0.7 % estimated
(%)	
Flammability limit –	5 % estimated
upper (%)	
Explosive limit – lower	Not available
(%)	
Explosive limit – upper	Not available
(%)	
Vapor pressure	Not available
Vapor density	>1
Relative density	Not available
Solubility(ies)	
Solubility (water)	Not available
Partition coefficient	Not available
(n-octanol/water)	
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	150 – 500 cp
Viscosity temperature	77°F (25° C)
Other information	250 lb/lb male estimated
Molecular weight	250 lb/lb-mole estimated
Specific gravity	0.8295
10. Stability and reactivity Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport
Chemical stability	Stable at normal conditions
Possibility of hazardous	Hazardous polymerization does not occur
reactions	המצמו מסמג עסוידוורווצמנוסוו מסבא ווסג טנגעו
Conditions to avoid	Heat, flames and sparks
Incompatible materials	Strong oxidizing agents
Hazardous decomposition	Irritants. Carbon oxides, Sulphur oxides
products	
P. 044000	

DISSCO®

11. Toxicological information

Information on likely routes of exposure

Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure
Inhalation	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea
Skin contact	Frequent or prolonged contact may defat and dry the skin, leading to discomfort and
	dermatitis
Eye contact	May be irritating to eyes
Symptoms related to the	Not available
physical, chemical and	
toxicological characteristics	
Information on toxicological ef	ifects
Acute toxicity	Not available
Skin corrosion/irritation	May cause defatting of the skin, but is neither an irritant nor a sensitizer
Serious eye damage/eye	Not classified. May be irritating to eyes
irritation	
Respiratory or skin sensitizatio	n
Respiratory sensitization	Not available
Skin sensitization	Not a skin sensitizer
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic
Carcinogenicity	None of this product's components are listed by ACGIH, IARC, NIOSH, NTP or OSHA
	Evaluation of Carcinogenicity
ASPHALT (CAS 8052-42-	
-	ated Substances (29 CFR 1910.1001-1050)
Not listed	
Reproductive toxicity	Not classified
Specific target organ toxicity	Central nervous system
- single exposure	
Specific target organ toxicity	Not available
- repeat exposure	
Aspiration hazard	Not classified
Chronic effects	Prolonged exposure may cause chronic effects
12. Ecological information	
Ecotoxicity	Not expected to be harmful to aquatic organisms
Persistence and degradability	Not available
Bio-accumulative potential	Not available
Mobility in soil	Not available
Other adverse effects	Not available
13. Disposal considerations	
Disposal instructions	Dispose of contents/container in accordance with local/regional/national/international
·	regulations. If discarded, this product is considered a RCRA ignitable waste, D001
Hazardous waste code	D001: Waste Flammable material with a flash point <140° F
Waste from residues/	Dispose of in accordance with local regulations
unused products	·
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal

DISSCO®

14. Transport information DOT

DOT	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Special precautions for	Not available
user	
Special provisions	B1, B52, IB3, T4, TP1, TP29
Packaging exceptions	150
Packaging non bulk	203
Packaging bulk	242
ΙΑΤΑ	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(s)	
Class	3
Subsidiary risk	-
Packing group	III
Environmental hazards	No.
ERG Code	3L
Special precautions for	Not available
user	
Other information	
Passenger and cargo	Allowed
Aircraft	
Cargo aircraft only	Allowed
IMDG	
UN number	UN1999
UN proper shipping name	Tars, liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	111
Environmental hazards	
Marine pollutant	No
EmS	F-E, S-E*
Special precautions for	Not available
user	
Transport in bulk according to	Not available
Annex II of MARPOL 73/78	
And the IBC Code	

DOT



IATA; IMDG



15. Regulatory information	
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication
	Standard. 29 CFR 1910.1200
	CERCLA/SARA Hazardous Substances – Not applicable
TSCA Section 12(b) Export N	Notification (40 CFR 707, Subpart. D)
Not regulated	
CERCLA Hazardous Substan	ce List (40 CFR 302.4)
ASPHALT (CAS 8052-42-	4) Listed
•	ated Substances (29CFR 1910.1001-1050)
Not listed	
Superfund Amendments and	Reauthorization Act of 1986 (SARA)
Hazard categories	Immediate Hazard – Yes
-	Delayed Hazard – No
	Fire Hazard – Yes
	Pressure Hazard – No
	Reactivity Hazard – No
SARA 302 Extremely hazard	lous substance
Not listed	
SARA 311/312	Νο
Hazardous chemical	
SARA 313 (TRI reporting)	
Not regulated	
Other federal regulations	
Clean Air Act (CAA) Section	112 Hazardous Air Pollutants (HAPs) List
Not regulated	
-	112 [®] Accidental Release Prevention (40 CFR 68.130)
Not regulated	
Safe Drinking Water Act	Not Regulated
(SDWA)	
US state regulations	WARNING: This product contains a chemical known to the State of California to cause cancer
US Massachusetts RTK	– Substance List
ASPHALT (CAS 8052	2-42-4)
PETROLEUM NAPH	THA (CAS 8008-20-6)
US New Jersey Worker	and Community Right-to-Know Act
-	

DISSCO®

	PETROLEUM NAPH	THA (CAS 8008-20-6) 10000 LBS		
US Pennsylvania RTK – Hazardous Substances				
ASPHALT (CAS 8052-42-4)				
	PETROLEUM NAPHTHA (CAS 8008-20-6)			
	US Rhode Island RTK			
Not regulated				
US California Proposition 65				
US – California Proposition 65 – CRT: Listed date/Carcinogenic substance				
ASPHALT (CAS 8052-42-4) Listed: January 1, 1990				
International Inventories				
	Country(s) or region	Inventory name On inventory (yes /no)*	
	Australia	Australian Inventory of Chemical Substances (AICS)	Yes	
	Canada	Domestic Substances List (DSL)	Yes	
	Canada	Non-Domestic Substances List (NDSL)	No	
	China	Inventory of Existing Chemical Substances in China (IECSC)	Yes	
	Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes	
	Europe	European List of Notified Chemical Substances (ELINCS)	No	
	Japan	Inventory of Existing and New Chemical Substances (ENCS)	No	
	Korea	Existing Chemicals List (ECL)	Yes	
	New Zealand	New Zealand Inventory	Yes	
	Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes	
	United States & Puerto	Rico Toxic Substances Control Act (TSCA) Inventory	Yes	
*A "Yes" indicates tha		all components of this product comply with the inventory requirements administ	tered by the	
governing country(s)				
A "No" indicated that o		one or mor components of the product are not listed or exempt from listing on th	e inventory	
administered by the governing country(s)				
16. Other information, including date of preparation or last revision				
Issue		12-11-2014		
Versio	on #	01		
References		ACGIH		
		EPA: AQUIEW database		
		NLM: Hazardous Substances Data Base		
		US. IARC Monographs on Occupational Exposures to Chemical Agents		
		HSDB [®] - Hazardous Substances Data Bank		
		IARC Monographs. Overall Evaluation of Carcinogenicity		
		National Toxicology Program (NTP) Report on Carcinogens		
Disclaimer		ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices		
		The information provided in this Safety Data Sheet is correct to the best of our knowledge,		
		information and belief at the date of its publication. The information given is designed only		
		as a guidance for safe handling, use, processing, storage, transportation, disposal and release		
		and is not to be considered a warranty or quality specification. The information relates only		
		to the specific material designated and may not be valid for such material used in		
		combination with any other materials or in any process, unless specified in the	text.	

DISSCO®