# **PRODUCT INFORMATION SHEET**

## TITAN FOAM<sup>™</sup> Bi-Cellular Polyethylene Foam Backer Rod

IMPORTANT INFORMATION: Flexible polyethylene is an "article", not a chemical, as defined in 29 CFR 1910.1200©. It does not require a Safety Data Sheet under OSHA's Hazard Communication Standard. As a service to our customers, however, Backer Rod Mfg. Inc. has produced this Product Information Sheet.

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION		
Date of Preparation	: August 1, 2018	
Product Name	: Titan Foam <sup>™</sup> bi-cellular polyethylene foam backer rod	
Other Names	: Bi-cellular low density polyethylene foam (LDPE)	
Manufacturer Name	: Bay Foam Products Inc 2240 West Peoria Ave. Phoenix, AZ 85029 Tel: 602-943-4151 www.bayfoamproducts.com	
SECTION 2 - PHYSICAL AND CHEMICAL CHARACTERISTICS		

Since flexible polyethylene foam is a solid, physical characteristics such as boiling point, vapor pressure, vapor density evaporation rate, etc., do not apply.

Appearance	: Cellular flexible material, light brown in color. May also be in various colors.	
Density Solubility in Water	: 1.25 - 2 lbs per cu. ft. : Insoluble	
Stability and Reactivity	<ul> <li>Stable. No hazardous polymerization will occur in normal use.</li> <li>Prolonged exposure to temperatures in excess of 196°F may cause some loss of volatile components (e.g., flame retardants) through evaporation.</li> <li>Unprotected polyethylene foam will discolor and degrade under prolonged exposure to UV light.</li> <li>Solvent resistance will vary with solvent type.</li> </ul>	
SECTION 3 - FIRE HAZARD INFORMATION		
Auto Invition Daint		

Auto-Ignition Point:

: 343°F (ASTM D 1929)

## TITAN FOAM<sup>™</sup> Bi-Cellular Polyethylene Foam Backer Rod

	SECTION 3 - FIRE HA	ZARD INFORMATION cont.	
Fire Hazard	: WARNING: Polyethylene Foam will burn if exposed to an open flame or other sufficient heat source. Do not expose polyethylene foam to open flames or any other direct or indirect high temperature ignition source such as burning operations, welding, space heaters or naked lights.		
	consuming oxygen a deficiency of oxygen Hazardous gasses re	hylene foam will burn rapidly, releasing great heat and t a high rate. In an enclosed space the resulting will present a danger of suffocation to the occupants. leased by the burning foam can be incapacitating or fatal nhaled in sufficient quantities.	
	appear to be extingu	hylene foam is difficult to extinguish. Foam fires that iished may smolder and re-ignite. Always have fire vheather a fire has been extinguished.	
	High concentrations	n be readily ignite and presents a potential fire hazzard. of foam dust in the air can ge a potential explosion hazard sparks, or other ignition sources.	
Extinguishing Media	: Water spray, dry chemical, foam of carbon dioxide		
Fire-fighting Protection	• • •	el must be equipped with self contained breathing d fire-fighting clothing.	
	SECTION 4 -	HEALTH HAZARDS	
Exposure Limits	: None Established		
Acute Toxicity	: Skin Absorbtion : Swallowing : Inhalation : Skin Contact	Not likely. Non irritating None determined Inhalation of foam dust may cause irritation to nose, throat, and lungs Non irritating	
	: Eye Contact	Foam dust may cause eye irritaion or injury	

#### **SECTION 5 - HANDLING AND STORAGE**

: Keep foam away from sparks, naked lights, open flames, exposed electrical elements, or other ignition sources. Smoking should be forbidden in areas where material is stored or processed.

: Maintain adequate sprinkler protection where large volumes of foam are kept (e.g., warehouses, fabrication areas and storage rooms). Check for compliance with insurance regulations, local building codes or other legal requirements.

### SECTION 5 - HANDLING AND STORAGE cont.

- : Never use foam as an exposed interior wall or ceiling finish
- : Maintain sufficient aisle space to permit access for fire-fighting equipment and personnel to all foam storage areas.
- : Do not allow cuttings or foam scrap to accumulate.
- : Be aware that terms sometimes used to describe polyethylene foam, like "fire retardant" and "flame resistant", do not mean fire safety under all conditions. Flammability ratings from small-scale laboratory tests are not bo be taken as an indication of the materials behavior under actual fire conditions.

#### SECTION 6 - PERSONAL PROTECTION AND EXPOSURE CONTROLS

Protective Equipment	: Unless exposure to foam dust is anticipated, dust masks, goggles, and gloves are not required. Long sleeves are recommended if arms are repeatedly rubbed against foam.
Ventilation	: Mechanical ventilation should be considered in operations that generate abnormal quantities of foam dust, or where thermal decomposition of the foam occurs (e.g., hot-wire cutting, heat sealing, hot stamping and flame laminating.)
	SECTION 7 - EMERGENCY AND FIRST AID PROCEDURES
Skin	: Wash off any foam dust.

JKIII	. Wash on any roam dust.
Eyes	: Flush thouroughly with water.
Ingestion	: None necessary unless throat is obstructed
Inhalation	: Consult physician if coughing, discomfort, or obstruction of air passage occurs.

The information presented here is offered for your consideration, investigation and verification. The information is presented in good faith and was obtained from sources Bay Foam Products Inc believes to be reliable. Bay Foam Products Inc, however, makes no representation as to the completeness and accuracy. Bay Foam Products Inc makes no warranty, expressed or implied, with respect to the information contained herein.

Bay Foam Products Inc. cannot anticipate all conditions under which this information and the product may be used. The conditions of handling, storage, use, and disposal of the product are beyond Bay Foam Products Inc's control. Thus, we expressly disclaim responsibility or liablility for any loss, damage or expense arising out of reliance on the information contained herein. You are advised to make your own determination as to safety, suitability and appropriate manner of handeling, storage, use and disposal.